

09-22-00

SIEMENS

Express Mail Label No.: EF040550584US

UTILITY PATENT

Case Docket No.: 00P7901US

Date: 09/20/00

Date of Deposit: 09/20/00

Box PATENT APPLICATION
 Assistant Commissioner for Patents
 Washington, D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of:

Siemens Westinghouse Power Corporation

Inventor(s): ROBERT A. WARD
 MEHRZAD TARTIBI

For (title): COIL SUPPORT FINGER PLATE FOR STATOR OF POWER GENERATOR
 AND ASSOCIATED METHODS

This application includes:

19 pages: specification, claims, abstract, and title page
5 sheets of drawings, X formal/___informal containing Figures 1-6

Also enclosed is:

X Declaration and Power of Attorney
X An assignment of the invention to Siemens Westinghouse Power Corporation
 ___ A certified copy of a ___ application.
 ___ Information Disclosure Statement pursuant to 37 CFR 1.56.

The filing fee has been calculated as shown below:

				FEE	
BASIC FEE OTHER THAN SMALL ENTITY				\$ 690	

TOTAL CLAIMS		EXTRA			
<u>23</u>	- 20	=	<u>3</u>	x \$18.00	= \$ <u>54</u>

INDEP CLAIMS					
<u>4</u>	- 3	=	<u>1</u>	x \$78.00	= \$ <u>78</u>

*MULTIPLE DEPENDENT CLAIM PRESENTED + \$260.				=	\$ 0

TOTAL				\$ 822	

09/20/00
 JC931 U.S. PTO


JC515 U.S. PTO
 09/666684
 09/20/00

09/20/00 09/20/00 09/20/00

- X Please charge my Deposit Account No. 19-2179 in the amount of \$822
A duplicate copy of this sheet is enclosed.
- X The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 19-2179.
A duplicate copy of this sheet is enclosed.
- X Any additional filing fees required under 37 CFR 1.16.
- X Any patent application processing fees under 37 CFR 1.17.
- X The Commissioner is hereby authorized to charge payment of the following fees during the pendency of this application or credit any overpayment to Deposit Account No. 19-2179.
A duplicate copy of this sheet is enclosed.
- X Any patent application processing fees under 37 CFR 1.17.
- X Any filing fees under 37 CFR 1.16 for presentation of extra claims.

All correspondence related to this application should be sent to:

Siemens Corporation
Intellectual Property Department
186 Wood Avenue South
Iselin, NJ 08830
Tel. (908) 321-3026



Erik C. Swanson
Registration No. 40,194
(407)-736-5602

Dated: 09/20/00

00222-1399990

APPLICATION FOR LETTERS PATENT OF THE UNITED STATES

ROBERT A. WARD
1662 WOODLAND DRIVE
ROCKLEDGE, FL 32955

MEHRZAD TARTIBI
3224 ARDEN VILLAS BLVD. #14
ORLANDO, FL 32817

COIL SUPPORT FINGER PLATE FOR STATOR OF POWER GENERATOR
AND ASSOCIATED METHODS

TO WHOM IT MAY CONCERN, THE FOLLOWING IS A SPECIFICATION OF THE
AFORESAID INVENTION

COIL SUPPORT FINGER PLATE FOR STATOR OF POWER GENERATOR
AND ASSOCIATED METHODS

Field of The Invention

This invention is related to the power generation industry and, more particularly, to the field of turbine generators.

5

Background of the Invention

In the power generation industry, turbine generators conventionally include a stator and a rotor. The stator 10 often includes a finger plate 20 having a base 21 and a plurality of spaced-apart fingers 23, 24 connected to and extending radially inwardly, as understood by those skilled in the art, from the base 21 as shown in the prior art of FIGS. 1-2. The fingers 23, 24 of the finger plate 20 extend radially inwardly between stator coil slots 30 formed in laminations 35 of the stator 10. Conventionally, as illustrated, the stator coil slots 30 have a pair of stator coils 33, 34, e.g., one overlying the other, positioned in the slot 30. The stator coil 33 closest to the finger plate base 21 was then only

supported by side walls 31, 32 of the step irons and the bottom 19 of the stator slot 30 as shown.

Problems with this prior art type of finger plate 20 have been discovered, however. As shown in FIGS. 1-2, for these types of finger plates there is no contact between the base 21 of the finger plate 20 and the bottom of the coil 33 closest to the base 21 of the finger plate 20. During use, excessive vibrations within the stator coils 33, 34 can cause the deterioration of the stator coils 33, 34 and associated support structure. Also, stator slot wedges which assist in retaining the stator slot contents within the stator coil slot 30 can be desired to be used at the finger plate. The prior art finger plate 20, however, provides no support for mounting or positioning stator slot wedges within the stator coil slot 30 around the finger plate 20.

Summary of the Invention

In view of the foregoing, the present invention advantageously provides a stator having a coil support finger plate which radially supports contents of a stator core coil slot. The present invention also advantageously provides a coil support finger plate for a stator and associated methods which substantially reduces the vibrations associated with conventional finger plate designs and thereby decreases stress or strain to stator coil insulation and reduces component failure. The present invention additionally advantageously provides a coil support finger plate which effectively extends the length of the stator coil slot or winding basket. The present invention further advantageously provides a finger plate for a stator which has wedge lands defined by portions of the fingers of the finger plate for mounting or positioning stator slot wedges therein so that the

stator coils can then be supported by top or outer and bottom or inner portions of the finger plate as well.

More particularly, the present invention provides a stator for a power generator. The stator preferably has a plurality of laminations having a plurality of spaced-apart stator coil slots formed therein and stator coil slot contents positioned in each of the plurality of stator coil slots. The stator coil slot contents preferably include at least one stator coil. The stator also preferably has a coil support finger plate positioned at an end portion of the plurality of stator coil slots. The coil support finger plate has a base and a plurality of fingers extending outwardly from the base between the plurality of spaced-apart stator coil slots. The base includes a stator slot contents support portion positioned to underlie the stator slot contents and to support the stator coil slot contents thereon so that the stator slot contents support portion defines a stator slot bottom at the coil support finger plate.

Also, the present invention provides a coil support finger plate for a stator of a power generator. The coil support finger plate preferably includes a base and a plurality of fingers extending outwardly from the base so that at least one of the plurality of fingers also extends between end portions of a pair of stator coil slots when positioned adjacent thereto. The base preferably includes a stator slot contents support portion positioned to underlie contents of a stator coil slot and to radially support the stator coil slot contents thereon. The stator slot contents includes at least one stator coil.

Additionally, according to another aspect of the present invention, a coil support finger plate for a stator of a power generator is provided which preferably has a base and a plurality of fingers extending outwardly from the base so that at least one of the plurality of fingers also extends between end portions of a pair of stator coil slots when positioned adjacent thereto. The

at least one of the plurality of fingers has a distal end portion thereof being positioned adjacent distal side peripheries of each of the end portions of the pair of stator coil slots and medial portions of the at least one of the plurality of fingers extending along only side peripheries of one of end portions of the pair of stator coil slots. Wedge lands for each of the pair of stator coil slots are formed in or defined by at least portions of the at least one of the plurality of fingers.

Further, the present invention provides a method for supporting a stator slot coil to thereby reduce vibrations within a stator. The method preferably includes radially supporting the bottom of the contents of a stator coil slot by the use of a coil support finger plate having a base portion thereof which defines a stator coil slot bottom. The method can also include positioning first and second stator coil slot wedges each to overlie a corresponding one of end portions of first and second stator coil slots and in first and second spaced-apart, wedge lands formed in the coil support finger plate. The first wedge land for the first wedge is preferably formed in a distal end portion of at least one finger of the coil support finger plate extending between end portions of the first and second stator coil slots. The second wedge land for the second wedge is preferably formed in the distal end portion of the same at least one finger of the coil support finger plate.

Brief Description of the Drawings

Some of the features, advantages, and benefits of the present invention having been stated, others will become apparent as the description proceeds when taken in conjunction with the accompanying drawings in which:

FIG. 1 is a fragmentary front elevational view of a stator having a finger plate according to the prior art;

FIG. 2 is a fragmentary perspective view of a stator having a finger plate according to the prior art;

FIG. 3 is a fragmentary front elevational view of a stator having a coil support finger plate according to the present invention;

FIG. 4 is a sectional view of a stator having a coil support finger plate taken along line 3-3 of FIG. 2 according to the present invention;

FIG. 5 is a fragmentary front elevational view of a stator having a coil support finger plate according to the present invention; and

FIG. 6 is a fragmentary perspective view of a stator having a coil support finger plate according to the present invention.

Detailed Description of Preferred Embodiments

The present invention will now be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the illustrated embodiments set forth herein. Rather, these illustrated embodiments are provided so that this disclosure will be thorough and complete, and will fully convey the scope of the invention to those skilled in the art. Like numbers refer to like elements throughout, and prime and double prime notation, if used, indicate similar elements in alternative embodiments.

FIGS. 3-6 illustrate portions of a stator 10' having a coil support finger plate 20' for the stator 10' of a turbine generator according to the present invention. A stator 10 for a power or turbine generator is well known to those skilled in the art and, for brevity purposes, much of the additional details of the present stator 10' outside of the novel aspects emphasized will not be described herein. The stator 10' of the present invention is improved by having a novel coil support finger plate

20' as illustrated and described further herein. The stator 10' preferably has a plurality of laminations 35' having a plurality of spaced-apart stator coil slots 30' formed therein and stator coil slot contents 40 positioned in each of the plurality of stator coil slots 30'. The stator coil slot contents 40 preferably include at least one stator coil 43, and more preferably a pair of adjacent stator coils 43, 44 as shown. A first stator coil 43 of the pair preferably overlies (or underlies depending on the orientation of the stator) and abuttingly contacts a conformable material layer 41, e.g., conforms to stress, pressure, or weight to in the shape of the coil or other overlying structure, and a second stator slot coil 44 overlies the first stator slot coil 43 within the stator coil slot 30'. A coil spacer 42 is preferably positioned between the first and second slot coils 43, 44 as shown. The stator coil slot contents 40 can also advantageously include additional spacers 46 and slot fillers or filler blocks 48 positioned to overlie or distally extend from the second stator coil 44.

The stator 10 also preferably has a coil support finger plate 20' positioned at an end portion of the plurality of stator coil slots 30'. The coil support finger plate 20' has a base 21' and a plurality of fingers 26, 27 extending outwardly from the base 21' between end portions of the plurality of spaced-apart stator coil slots 30'. Unlike the prior art as shown in FIGS. 1-2, the base 21' of the coil support finger plate 20' includes a stator slot contents support portion 25 positioned to underlie the stator slot contents 40 and to support the stator coil slot contents 40 thereon so that the stator

slot contents support portion 25 defines a stator slot bottom at the coil support finger plate 20' (see FIG. 3). Although the stator slot of the prior art had a bottom, it did not have a bottom at the finger plate 20 (see FIGS. 1-5 2).

As perhaps best illustrated in FIGS. 3-4, the stator slot contents 40 abuttingly contact the stator slot bottom 25 so that the stator slot bottom 25 of the coil support finger plate 20' radially supports the stator slot contents 40. The stator slot contents 40 preferably include a layer 41 of readily conformable material, e.g., provided by a cushion of material, e.g., formed of Dacron and resin in a sealed Mylar bag or container, underlying the at least one stator coil 43 to enhance protection of the at least one stator coil 43 from the outer surface of the stator slot bottom 25. In other words, the conformable layer 41 readily conforms and shapes to the outer contours of the coil 43 to provide cushioning support when resting on or contacting the bottom 25. The conformable material layer 41 preferably overlies and abuttingly contacts the stator slot bottom 25 and underlies and abuttingly contacts the stator coil 43 positioned closest to the base 21' of the coil support finger plate 20' so that the stator slot bottom 25 supports both the conformable material layer 41 and the at least one stator coil 43, as well as other slot contents 40, at the coil support finger plate 20'.

As shown in FIGS. 3 and 5-6, the plurality of fingers 26, 27 of the coil support finger plate 20' includes a plurality of spaced-apart pairs of fingers 26, 27. The stator coil slot bottom 25 is positioned between each of

the plurality of spaced-apart pairs of fingers, e.g., 26, 27, and 26, 27 and at least a pair of fingers 26, 27 of the plurality of fingers of the coil support finger plate each extend outwardly between an adjacent pair of the plurality of spaced-apart stator coil slots 30' and 30'.
 5 The at least a pair of fingers includes first 26 and second 27 fingers. Distal end portions of the first finger 26 extend outwardly a greater distance from the base 21' than the second finger 27.

10 The first and second fingers 26, 27 are spaced-apart from each other, and the greater-distance extending distal end portions of first finger 26 are positioned adjacent distal side peripheries 31', 32' of each of the adjacent pair of stator coil slots 30' (i.e., when viewed from the
 15 ends of the stator coil slots 30' or from a front elevational view of the finger plate 20') and spaced-apart from distal end portions of the second finger 27. Medial portions of the first finger 26 extends along only side peripheries 32' of one of the pair of stator coil slots
 20 30' or the step irons (i.e., when viewed from the ends of the stator coil slots 30' or from a front elevational view of the finger plate 20'), and the second finger 27 extends along only side peripheries 31' of another one of the pair of stator coil slots 30' (i.e., when viewed from the ends
 25 of the stator coil slots 30' or from a front elevational view of the finger plate 20').

This configuration of the first and second fingers 26, 27 advantageously allows the distal end portions of the first finger 26 to have a first wedge land 28 formed
 30 in a region thereof adjacent the one of the pair of stator slot coils 30', and the spaced-apart region between the

distal end portions of the second finger 27 and the distal end portions of the first finger 26 define a second wedge land 29 for the another one of the pair of stator coil slots 30' so that the first wedge land 28 for the one stator slot 30' is formed by a first pair of fingers 26, 27 having first and second fingers thereof and the second wedge land 29 for the one stator slot 30' is formed by a second pair of fingers 26, 27 having first and second fingers thereof. The first and second wedge lands 28, 29 together in combination are spaced-apart as shown and define a wedge land. The second wedge land 29 preferably includes an extended wedge capture region 52 positioned to capture extended regions of a wedge 50 when positioned therein to thereby enhance the securing of the wedge 50 within the first and second wedge lands 28, 29, if so desired. As understood by those skilled in the art, the finger plate 20' advantageously has wedge lands 28, 29 defined by portions of the fingers of the finger plate for mounting or positioning stator slot wedges 50 therein so that the stator coils can then be supported by both top or inner and bottom or outer portions of the finger plate 20' as well.

As illustrated in FIGS. 3-6, the present invention also provides a method for supporting a stator coil 43 or stator slot contents 40 to thereby reduce vibrations within a stator 10'. The method preferably includes radially supporting the bottom 25 of the contents 40 of a stator coil slot 30' by the use of a coil support finger plate 20' having a base portion thereof which defines a stator coil slot bottom 25. The method can also include positioning first and second stator coil slot wedges 50

and 50 each to overlies a corresponding respective one of first and second stator coil slots 30' and 30' and in first and second spaced-apart, wedge lands 28, 29 formed in the coil support finger plate 20'. The first wedge land 28 for the first wedge 50 is preferably formed in a distal end portion of at least one finger 26 of the coil support finger plate 20' extending between the first and second stator coil slots 30' and 30'. The second wedge land 29 for the second wedge 50 is preferably formed in the distal end portion of the same at least one finger 26 (see, e.g., phantom lines of FIG. 5) of the coil support finger plate 20'. The method can further include the at least one finger 26 also having medial portions thereof which extend along side peripheries 32 of only one of the first and second stator coil slots 30'.

Many modifications and other embodiments of the invention will come to the mind of one skilled in the art having the benefit of the teachings presented in the foregoing descriptions and the associated drawings. Therefore, it is to be understood that the invention is not to be limited to the specific embodiments disclosed, and that modifications and embodiments are intended to be included within the scope of the appended claims.

THAT CLAIMED IS:

1. A stator for a power generator, the stator comprising:

a plurality of laminations having a plurality of spaced-apart stator coil slots formed therein;

5 stator coil slot contents positioned in each of the plurality of stator coil slots, said stator coil slot contents including at least one stator coil;

a coil support finger plate positioned at an end portion of the plurality of stator coil slots, the coil support finger plate having a base and a plurality of fingers extending outwardly from the base between the plurality of spaced-apart stator coil slots, the base including a stator slot contents support portion positioned to underlie end portions of the stator slot contents and to support the end portions of the stator coil slot contents thereon so that the stator slot contents support portion defines a stator slot bottom at the coil support finger plate.

10
15

2. A stator as defined in Claim 1, wherein the end portions of the stator slot contents abuttingly contact the stator slot bottom so that the stator slot bottom of the coil support finger plate radially supports the stator slot contents.

5

3. A stator as defined in Claim 1, wherein the stator slot contents include a layer of readily conformable material underlying the at least one stator coil to enhance protection of the at least one stator coil from the outer surface of the stator slot bottom, and wherein the conformable material layer overlies and abuttingly contacts the stator slot bottom and underlies and abuttingly contacts the at least one stator coil so that the stator slot bottom supports both the conformable material layer and the at least one stator coil.

5
10

4. A stator as defined in Claim 3, wherein the at least one stator coil comprises a first stator slot coil overlying and abuttingly contacting the conformable material layer and a second stator slot coil overlying the first stator slot coil within the stator slot.

5. A stator as defined in Claim 1, wherein the plurality of fingers includes a plurality of spaced-apart pairs of fingers, wherein the stator coil slot bottom is positioned between each of the plurality of spaced-apart pairs of fingers, and wherein at least a pair of fingers of the plurality of fingers of the coil support finger plate each extend outwardly between an adjacent pair of end portions of the plurality of spaced-apart stator coil slots, the at least a pair of fingers including first and second fingers, distal end portions of the first finger extending outwardly a greater distance from the base than the second finger.

6. A stator as defined in Claim 5, wherein the first and second fingers are spaced-apart from each other and the greater-distance extending distal end portions of first finger being positioned adjacent distal side peripheries of each of the adjacent pair of end portions of stator coil slots and spaced-apart from distal end portions of the second finger, wherein medial portions of the first finger extends along only side peripheries of one of the end portions of the pair of stator coil slots, and wherein the second finger extends along only side peripheries of another one of the end portions of the pair of stator coil slots.

7. A stator as defined in Claim 6, wherein the distal end portions of the first finger has a first wedge land formed in a region thereof adjacent the one of the

end portions of the pair of stator slot coils, and wherein
 5 the spaced-apart region between the distal end portions of
 the second finger and the distal end portions of the first
 finger define a second wedge land for the another one of
 the end portions of the pair of stator coil slots so that
 the first wedge land for the end portion of the one stator
 10 slot is formed by a first pair of fingers having first and
 second fingers thereof and the second wedge land for the
 end portion of the one stator slot is formed by a second
 pair of fingers having first and second fingers thereof.

8. A stator as defined in Claim 7, wherein the
 second wedge land includes an extended wedge capture
 region positioned to capture extended regions of a wedge
 when positioned therein to thereby enhance the securing of
 5 the wedge within the first and second wedge lands.

9. A coil support finger plate for a stator of a
 power generator, the coil support finger plate comprising:
 a base; and

a plurality of fingers extending outwardly from the
 5 base so that at least one of the plurality of fingers also
 extends between end portions of a pair of stator coil
 slots when positioned adjacent thereto, and

wherein the base includes a stator slot contents
 support portion positioned to underlie contents of an end
 10 portion of a stator coil slot and to radially support the
 stator coil slot contents thereon, the stator slot
 contents including at least one stator coil.

10. A coil support finger plate as defined in Claim
 9, wherein the end portions of the stator slot contents
 abuttingly contact the stator slot contents support
 portion when positioned within a stator coil slot having
 5 the coil support finger plate so that the stator slot

contents support portion defines a stator slot bottom at the coil support finger.

11. A coil support finger plate as defined in Claim 10, wherein the stator slot contents include a layer of readily conformable material underlying the at least one stator coil to enhance protection of the at least one stator coil from the outer surface of the stator slot bottom, and wherein the conformable material layer overlies and abuttingly contacts the stator slot bottom and underlies and abuttingly contacts end portions of the at least one stator coil so that the stator slot bottom supports both the conformable material layer and the at least one stator coil.

12. A coil support finger plate as defined in Claim 11, wherein the plurality of fingers includes a plurality of spaced-apart pairs of fingers, wherein the stator coil slot bottom is positioned between each of the plurality of spaced-apart pairs of fingers, and wherein at least a pair of fingers of the plurality of fingers of the coil support finger plate each extend outwardly between an adjacent pair of end portions of a plurality of spaced-apart stator coil slots of a stator, the at least a pair of fingers including first and second fingers, distal end portions of the first finger extending outwardly a greater distance from the base than the second finger.

13. A coil support finger plate as defined in Claim 12, wherein the first and second fingers are spaced-apart from each other and the greater-distance extending distal end portions of first finger being positioned adjacent distal side peripheries of each of the adjacent pair of end portions of stator coil slots and spaced-apart from distal end portions of the second finger, wherein medial portions of the first finger extends along only side

peripheries of one of the pair of stator coil slots, and
 10 wherein the second finger extends along only side
 peripheries of another one of the pair of stator coil
 slots.

14. A coil support finger plate as defined in Claim
 13, wherein the distal end portions of the first finger
 has a first wedge land formed in a region thereof adjacent
 the one of the end portions of the pair of stator slot
 5 coils, and wherein the spaced-apart region between the
 distal end portions of the second finger and the distal
 end portions of the first finger define a second wedge
 land for the another one of the end portions of the pair
 of stator coil slots so that the first wedge land for the
 10 one stator slot is formed by a first pair of fingers
 having first and second fingers thereof and the second
 wedge land for the one stator slot is formed by a second
 pair of finger having first and second fingers thereof.

15. A coil support finger plate as defined in Claim
 14, wherein the second wedge land includes an extended
 wedge capture region positioned to capture extended
 regions of a wedge when positioned therein to thereby
 5 enhance the securing of the wedge within the first and
 second wedge lands.

16. A coil support finger plate for a stator of a
 power generator, the coil support finger plate comprising:
 a base; and

a plurality of fingers extending outwardly from the
 5 base so that at least one of the plurality of fingers also
 extends between end portions of a pair of stator coil
 slots when positioned adjacent thereto, the at least one
 of the plurality of fingers having a distal end portion
 thereof being positioned adjacent distal side peripheries

10 of each of the end portions of the pair of stator coil slots and medial portions of the at least one of the plurality of fingers extending along only side peripheries of one of the end portions of the pair of stator coil slots.

17. A coil support finger plate as defined in Claim 16, wherein the plurality of fingers includes a plurality of spaced-apart pairs of fingers, wherein the at least one finger comprises at least a pair of fingers, and wherein
5 the at least a pair of fingers of the plurality of fingers of the coil support finger plate each extend outwardly between an adjacent pair of end portions of a plurality of spaced-apart stator coil slots of a stator, the at least a pair of fingers including first and second fingers,
10 distal end portions of the first finger extending outwardly a greater distance from the base than the second finger.

18. A coil support finger plate as defined in Claim 17, wherein the first and second fingers are spaced-apart from each other and the greater-distance extending distal end portions of first finger being positioned adjacent
5 distal side peripheries of each of the adjacent pair of the end portions of stator coil slots and spaced-apart from distal end portions of the second finger, wherein medial portions of the first finger extends along only side peripheries of one of the end portions of the pair of
10 stator coil slots, and wherein the second finger extends along only side peripheries of another one of the end portions of the pair of stator coil slots.

19. A coil support finger plate as defined in Claim 18, wherein the distal end portions of the first finger has a first wedge land formed in a region thereof adjacent the one of the pair of stator coils, and wherein the

5 spaced-apart region between the distal end portions of the
second finger and the distal end portions of the first
finger define a second wedge land for the another one of
the end portions of the pair of stator coil slots so that
the first wedge land for the one stator slot is formed by
10 a first pair of fingers having first and second fingers
thereof and the second wedge land for the one stator slot
is formed by a second pair of fingers having first and
second fingers thereof.

20. A coil support finger plate as defined in Claim
19, wherein the second wedge land includes an extended
wedge capture region positioned to capture extended
regions of a wedge when positioned therein to thereby
5 enhance the securing of the wedge within the first and
second wedge lands.

21. A method for supporting a stator coil to thereby
reduce vibrations within a stator, the method comprising:
radially supporting the bottom of end portions of the
contents of a stator coil slot by the use of a coil
5 support finger plate having a base portion thereof which
defines a stator coil slot bottom.


22. A method as defined in Claim 21, further
comprising positioning first and second stator slot wedges
each to overlie a corresponding one of end portions of
first and second stator coil slots and in first and second
5 spaced-apart, wedge lands formed in the coil support
finger plate, the first wedge land for the first wedge
being formed in a distal end portion of at least one
finger of the coil support finger plate extending between
end portions of the first and second stator coil slots and
10 the second wedge land for the second wedge being formed in
the distal end portion of the same at least one finger of
the coil support finger plate.

23. A method as defined in Claim 22, wherein the at least one finger also has medial portions thereof which extend along side peripheries of only one of the end portions of the first and second stator coil slots.

**COIL SUPPORT FINGER PLATE FOR STATOR OF POWER GENERATOR
AND ASSOCIATED METHODS**

Abstract Of The Disclosure

A stator (10') for a power generator having a coil support finger plate (20') and associated methods are provided. The stator (10') preferably has a plurality of laminations or step irons having a plurality of spaced-apart stator coil slots (30') formed therein and stator coil slot contents (40) positioned in each of the plurality of stator coil slots (30'). The stator coil slot contents (40) preferably include at least one stator coil (43). The stator (10') also preferably has a coil support finger plate (20') positioned at an end portion of the plurality of stator coil slots (30'). The coil support finger plate (20') has a base (21') and a plurality of fingers (26, 27) extending outwardly from the base (21') between the plurality of spaced-apart stator coil slots (30'). The base (21') includes a stator slot contents support portion (25) positioned to underlie end portions of the stator slot contents (40) and to support the end portions of the stator coil slot contents (40) thereon so that the stator slot contents support portion (25) defines a stator slot bottom at the coil support finger plate (20').

[illegible]

(PRIOR ART)

19

23

24

32

33

34

31






Fig. 4.




FIG. 5.




FIG. 6.

DECLARATION FOR PATENT APPLICATION & POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

COIL SUPPORT FINGER PLATE FOR STATOR OF POWER GENERATOR AND ASSOCIATED METHODS

the specification of which
 X is attached hereto, and
 was filed on _____ as Application Serial No. _____
and was amended on _____ (if applicable)

Listing of named inventor(s): **ROBERT A. WARD**

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Codes, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

PRIOR FOREIGN APPLICATION(S) Priority claimed

(Number)	(Country)	(Day/month/year filed)	Yes	No
(Number)	(Country)	(Day/month/year filed)	Yes	No

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below:

PROVISIONAL APPLICATION NUMBER FILING DATE

I hereby claim the benefits under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, we acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)	(Filing date)	(Status) (patented, pending, abandoned)
--------------------------	---------------	--

